

Primrose


IT task light

IT base model includes:

- Energy efficient T5 3500K fluorescent lamp
- Normal power factor electronic ballast
- 9' black power cord with 90° plug, sw rotation, right hand exit
- Black rocker switch, 2 position, center of fixture
- Linear prismatic (batwing) lens
- UV stable silver reflector
- Cord management kit
- Mounting hardware package - must specify
- Paint finish - must specify
- UL and CUL listed



Base Number	Suggested Panel Size	Actual Length	Lamp Wattage
IT 24	12"-24"	22.93"	14
IT 36	18"-36"	34.75"	21
IT 48	24"-48"	45.56"	28
IT 60	30"-60"	58.74"	35



Specifying notes:

- Specify a task light that is the same size as or longer than the width of the panel, see chart on next page.
- The standard cord exit on the IT is right hand (RH) from the bottom rear of the light fixture. This allows the fixture to be mounted end-to-end with another fixture and also provides easy cord management.
- Cord management kit includes 1 horizontal and 2 vertical clips.
- Additional cord management clips may be specified. See option prices on next page.
- See page 58 for manufacturer's cross reference codes. If the manufacturer and system name is not included on the mounting cross reference chart, specify the manufacturer, system name, and the width of the panel. A Light Corporation customer service rep will contact you with the availability of the mounting application.
- Cord covers are available in black (209), gray taupe (228), light tone (063), stone gray (062) and soft white (061); color code must be specified with size of cord cover.

Primrose

IT task light

IT base model prices

Base Number	Suggested Panel Size	Actual Length	List Price
IT 24	12"-24"	22.93"	\$ 279.00
IT 36	18"-36"	34.75"	289.00
IT 48	24"-48"	45.56"	306.00
IT 60	30"-60"	58.74"	323.00

Base Number	Recommended Panel Widths
IT 24	18", 24"
IT 36	18", 24", 30", 36"
IT 48	24", 30", 36", 42", 48"
IT 60	30", 36", 42", 48", 60"

Mounting options:

Panel (PM) brackets that slide along the back channel of the light allow it to mount to various office furniture system panels. The manufacturer and system name that the fixture will be mounting on must be specified when ordering.

Wall (WM) stud screws and flat brackets for mounting task light to the wall.

Cord cover color code

Finish	Code
Black	209
Gray taupe	228
Light tone	063
Stone gray	062
Soft white	061

How to specify the IT task light


Example IT 36 ELE 018 ST90

1. base number
2. hpf electronic ballast
3. paint finish
4. mounting code

IT option prices

Option	Description	Code	List Price
Lamp:	4100K	TRI41	\$ 0.00
Ballast:	High performance / High power factor electronic	ELE	40.00
Cord exit:	Left hand	LH	9.00
Cord rotation:	Straight plughead	SP	0.00
Cord color: <small>Available on straight cords only</small>	Gray Neutral	SPGR SPNL	8.00 8.00
City code: (Chicago)	Fused plug -sw rotation Fused plug -straight	CHC9SW CHC9ST	48.00 48.00
Cord manager:	Horizontal 2- 2" vertical 12" vertical Bag of 50 horizontal (CM1)	CM1 CM2 CM3 CM4	3.00 3.00 3.00 37.00
Cord cover:	24" cover (add color code) 48" cover (add color code)	CMC24 CMC48	13.00 21.00
Mounting:	Panel mount Wall mount	PM WM	0.00 22.00

When choosing options refer to pages 38-43 to verify proper use.



panel mount



wall mount

1. Specify base number for appropriate panel size.
2. Select option code from list.
3. Select paint finish from page 54.
4. Select code for manufacturer and system name of unit that the light will be mounting in, page 57.

If manufacturer and system name code is not listed, identify them on your purchase order and a Light Corporation customer service rep will contact you on availability.

Call Light Corporation customer service to place an order, 1-800-544-4899.
Prices are subject to change.